





RISORIUS Circular LED lighting designed for suspension

LIGHTING	COLOR TEMPERATURE OPTIONS		DIMENSIONS	MATERIALS
	EVO OPTION	ERG'O OPTION		
LED 17,955 lm 168 W Group 0 (compliant with NF EN 62 471 standard)  	5,000 °K <i>Light intensity controlled via Bluetooth remote control</i>	2,700 °K to 6,500 °K <i>Light intensity & color temperature controlled via Bluetooth remote control</i>	1,200 x 100 mm 4 points cable suspension Weight: 12.5 kg	Powder-coated aluminum structure Multiple color options available

ADVANTAGES & KEY FEATURES

- + Direct and indirect lighting for a softer glow
- + Ultra-modern design
- + No blue light peak, ensuring total photobiological safety
- + No degradation of light quality over time
- + No cast shadows
- + No stroboscopic effect, reducing headaches
- + Low power consumption, thus minimal heat
- + No maintenance, worry-free usage

DESTINATION

DENTAL OFFICES
 ORTHODONTIC OFFICES
 TREATMENT ROOMS
 RECEPTION
 WAITING ROOM

OUR WARRANTIES

Lighting: 5 years



Available colors

When placing your order, please specify the color you want for each luminaire

<p>CLASSIC COLORS</p>	 <p>SNOW WHITE 11</p>	 <p>IVORY WHITE 12</p>	 <p>RADIANT SILVER 13</p>	 <p>URBAN GRAPHITE 14</p>	 <p>JET BLACK 15</p>	
<p>PREMIUM COLORS*</p> <p><i>*Not available for the Amino luminaire</i></p>	 <p>SATIN PLATINIUM 31</p>	 <p>SATIN TITANIUM 32</p>	 <p>SATIN GOLD 33</p>	 <p>SATIN COPPER 34</p>	 <p>SATIN SEA 35</p>	 <p>SATIN SILVER 36</p>

Scan these QR codes to watch all our explanatory videos:

What is the circadian rhythm?



What is the difference between Ergo and Evo?



How does the remote control work?

